



## G1000

### Nav Data and Charts update procedures

1. Make sure you have a current Jeppesen subscription (navdata and charts)
2. Have a blank 1G SD card for downloading the navdata
3. Log onto Jeppesen Services and download the Navdata onto the blank SD card
4. Removed lower SD card from **MFD** and download electronic charts data onto this card from the Jeppesen Services program.
5. Reinstall lower SD card in **MFD**. This finishes electronic charts update.
6. With ground power applied to aircraft (and aircraft turned off) insert navdata card into top (empty slot) on pilots **PFD**.
7. Removed top card from **MFD** and put someplace safe.
8. pull circuit breakers for **MFD** and **copilot PFD**
9. Turn ground power on and turn avionics power on.
10. Follow on screen instructions to load new Navdata on **PFD**
11. After **PFD** restarts remove SD card from top slot of pilots **PFD** and install in top slot of **MFD**
12. Reset circuit breaker for **MFD** and follow on screen instruction to load Navdata into **MFD** (same as pilots PFD)
13. After **MFD** restarts removed SD card from top slot of **MFD** and install into top slot of copilot **PFD**
14. Reset circuit breaker for copilot **PFD** and follow on screen instructions to load Navdata into copilots **PFD** (same as MFD)
15. After copilot **PFD** restarts remove SD card from top slot and turn all avionics off
16. Reinstall original SD card into **MFD** and turn all avionics back on
17. Verify all updates have been loaded in the AUX pages of the **MFD**